



APPROVAL OF MANUFACTURER CERTIFICATE

Certificate No:
AMMM000026A
Revision No:
2

This is to certify:

That

Slévárny Trinec a.s.
Průmyslová 1001, 739 61 Třinec-Staré Město,
Czech Republic

is an approved manufacturer of
Steel Castings

in accordance with
DNV GL rules for classification – Ships

and the following particulars:

Application area	Castings for hull structures and equipment Castings for machinery Ferritic steel castings for low temperature service
Steel type	Carbon and carbon-manganese
Casting method	Sand casting
Max. weight	6 000 kg
Heat treatment condition	See page 2

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules.
Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at **Hamburg** on **2021-08-17**

for **DNV**

This Certificate is valid until **2024-08-31**.

DNV local station: **Prague CMC**

Approval Engineer: **Christian Wildhagen**

Thorsten Lohmann
Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Particulars of the approval

Castings for hull structure and equipment

Steel type	Grade ³⁾	Casting method ¹⁾	Max. weight [kg]	Heat treatment condition ²⁾
C and C-Mn	VL C400UW, VL C440UW, VL C480UW, VL C520UW, VL C560UW, VL C600UW	SC	6 000	N, NT, QT

Castings for machinery

Steel type	Grade ³⁾	Casting method ¹⁾	Max. weight [kg]	Heat treatment condition ²⁾
C and C-Mn	VL C400U, VL C440U, VL C480U, VL C520U, VL C560U, VL C600U	SC	6 000	N, NT, QT

Ferritic steel castings for low temperature service

Steel type	Grade ³⁾	Casting method ¹⁾	Max. weight [kg]	Heat treatment condition ²⁾
C and C-Mn	C450L, C490L	SC	6 000	N, NT, QT

Remarks:

- 1) SC: Sand Casting
- 2) N: Normalised
 QT: Quenched and tempered
 NT: Normalised and tempered
- 3) Incl. equivalent grades in acc. to other standards